



# Environmental Monitor

## Product Datasheet

### Environment monitoring with broad sensor set and additional options

Environment monitoring with integrated energy harvesting for long-life, maintenance-free operation. Ideal for monitoring of internal and external environments, including atmospheric and acoustic conditions. Optional cloud-based software platform for sensing that incorporates real-time data analysis, complete historic data storage and alerts for environmental conditions.

Model Options	Standard: IP rated enclosure for internal and external applications
Enclosure Style	
Enclosure Dimensions	W 130 x H 91 x D 63mm
Enclosure Mounting	Screw-fixing   Wall-fixing   Over Insulation Clips   Pipe Stand Off Pipe stand offs support direct mounting of sensor unit to high temperature pipework, with insulation and thermal barrier.
Enclosure Type	IP67 (Dust-tight + Immersion) Polycarbonate   UL 508   NEMA TYPE 4,4X,6,6P
Enclosure (Options)	Optional alternative enclosures available, including extra-high impact resistance polycarbonate and full metal enclosures.
Sensing (Standard)	Onboard environmental sensing Ambient temperature, humidity, pressure conditions and acoustic sensing. Including acoustic analysis and classification. Onboard orientation and position sensing Unit orientation, including movement, shock, and vibration detection.
Sensing (Options)	Environment sensing Additional environment specific sensing options include CO <sub>2</sub> , O <sub>3</sub> , NO <sub>x</sub> and other pollutant and contaminant sensing. Other sensing Environment Monitor supports a wide range of other sensing capabilities through pluggable sensing modules. A selection of the options available are listed in "Sensor Options" (below). Standard modules may be swapped or added to as required.
Power (Standard)	1x Solar Energy Harvesting Enclosure mounted solar panel with energy harvesting and on-board energy storage. Internal harvesting and power system fully monitored with power availability, power storage and backup power reporting. Energy storage onboard sub-system on board for overnight operation. Long-life backup battery for status reporting in case of unit being covered or damage to panel subsystem.
Power (Options)	Environment Monitor supports a wide range of other power sources through a system of pluggable modules. See a selection of available options listed in "Power Options" (below). Standard modules may be swapped or added to as required.
Status Indicators	1x Status indicator Unit status, power status and active operation indicators (Red, Green, Yellow colours – steady, pulsed and flashing statuses). 1x Communications indicator Communications status and TX/RX indicators (Red, Green, Yellow colours – steady, pulsed and flashing statuses).
Comms (Standard)	Selectable Mesh Radio (ISM 868/915 MHz) or LoRaWAN (ISM 868/915 MHz) support. Mesh radio requires one (or more) gateway units per site installation <sup>1</sup> . Gateways provide choice of cloud uplink (via Wi-Fi, Ethernet or 3G/4G/5G mobile data uplink <sup>2</sup> ). LoRaWAN radio requires LoRaWAN gateway, gateway is customer or DCO Systems provided <sup>3</sup> .

<sup>1</sup> DCO provided gateways are extra cost options. Minimum of one gateway per mesh network installation.

<sup>2</sup> 3G/4G/5G Cloud connectivity provided as part of cloud data analytics platform subscription (where taken)

<sup>3</sup> DCO Systems provided LoRaWAN gateway is an extra cost option.

Model Options	Standard: IP rated enclosure for internal and external applications
Comms (Options)	Environment Monitor supports a wide range of other communications options through a system of pluggable modules. See a selection of available options listed in “Communications Options” (below). Standard modules may be swapped or added to as required.
Processing	120MHz ARM M4 Processor with Hardware Floating Point and DSP Extensions
Storage (Standard)	64Kb F-RAM Onboard Non-volatile, high-endurance long term storage. State checkpoints and up to 8-hours data storage in event of network disruption.
Storage (Options)	Units support pluggable modules to extend on device data storage for storage of ultra-high-resolution data where required (e.g., raw high-speed sensor data prior to processing for FFT analysis).
Operational	Temperature: -20°C to 85°C   Relative Humidity: 5% to 100% (condensing)

## Sensor Options

Environment monitor is built on a modular platform and supports the wide range of physical sensing and integration options available from DCO Systems. We expand capabilities all the time – ask us about your requirement if not listed.

Air Quality and Pollution Monitoring	Volatile Organic Compound (VOC), Carbon Dioxide (CO <sub>2</sub> ), Ozone (O <sub>3</sub> ), Nitrogen Oxide (NO <sub>x</sub> ) and dust/particulate measurement – variants for internal and external monitoring applications.
Level and distance	Ultrasonic, Laser or Microwave distance and/or level sensing.
AC/DC Current, Voltage and Power	Current Transducers, Hall-Effect Sensors, and power monitoring (I + V).
Digital Inputs	Volt-free inputs, logic-level inputs, and pulse counter inputs (pulse counting meter compatible).
Analog Inputs	0-5V, 0-10V, 0-20mA and 4-20mA inputs with isolation support up to 4420 V <sub>RMS</sub> .
Precision Vibration and Movement	Precision accelerometer sensing for shock detection, movement alerting and vibration analysis.
High-Precision Temperature	RTD probes with grade support to Category A (±0.5°C FS Accuracy, RTD dependent).
Pressure Sensing	Differential, gauge, and absolute pressure sensing for pipework, ducting and air/fluid applications.

## Power Options

Environment monitor models are built on a modular platform and so support the wide range of power options available from DCO Systems. The range includes energy harvesting, fully battery powered, AC and DC power supply options. Power options are adaptable and flexible ask us about your requirement if it is not listed here.

Thermal harvesting	Integrated (on supported enclosures) or externally mounted solar thermoelectric harvesters with energy storage for intermittent and pulse operation (e.g., long range LoRaWAN transmission).
Electromagnetic energy harvesting	Electromagnetic energy harvesting from AC sources by with energy storage supporting intermittent harvesting and pulse power operation.
Fully battery powered operation	Self-contained solution with long-life Lithium-thionyl chloride (Li-SOCl <sub>2</sub> ) batteries with 10-year lifespan. Options for batteries with 20-year lifetime and extended temperature support.
AC/DC power modules	Direct power input from AC/DC sources from 5-745 VDC and 85-480 VAC. Isolated and non-isolated options depending on input voltage level and isolation requirements.

## Communications Options

Environment monitor models are built on a modular platform supporting a range of communications modules options. Communications options are constantly expanding, ask us about your requirement if it is not listed.

ISM Mesh Network	Mesh network operating in the Industrial, Scientific, and Medical (frequency varies by territory).
LoRaWAN Network	LoRaWAN compatible networking (frequency varies by territory) on public or private LoRaWAN networks.
NB-IoT / LTE-M	Operation on 4G and 5G networks supporting either NB-IoT or LTE-M capabilities.
Thread / Bluetooth Mesh / Wi-Fi	Thread, Bluetooth Mesh and Wi-Fi network support.
EtherCAT	Integration as an EtherCAT device into EtherCAT device networks.
Modbus / Modbus TCP	Integration as a Modbus device into Modbus device networks.